






Mobile *SpeedFusion™* VPN Endpoint



Turbocharged VPN Access. Anytime. Everywhere.

The Pepwave MAX On-The-Go bonds the bandwidth of up to four 4G LTE/ 3G USB modems using SpeedFusion technology to deliver secure and fast VPN connections anywhere you work. You can even create your own hotspot or boost your bandwidth with available Wi-Fi connections using built-in 802.11n networking, making the MAX On-The-Go the ultimate mobile connectivity solution.



Automatic WAN Failover. Uptime. All the Time.

Wherever you roam, the MAX On-The-Go keeps you online without interruption by automatically sensing connection status and switching between Ethernet WAN and up to 4G LTE / 3G links as needed. It all happens so quickly and seamlessly that you probably won't even notice occasional link connectivity issues.

Ultra Mobile. Ultra Tough, Too.

Compact and lightweight, the MAX On The-Go fits into any mobile workflow. And because it's built like a tank, it'll be ready to hit the road for years to come.

Multi-Voltage Design. Plug in Almost Anywhere.

Who says 12V DC is the only way to go mobile? The MAX On-The-Go supports input voltages from 10V DC to 24V DC, so you can plug in and get to work in a wider variety of environments.

Centralized Management. At Your Desk or From the Cloud.

Pepwave's intuitive local administration console and our InControl cloud management solution make it easy to take charge of your MAX On-The-Go from across the office or halfway around the world.

Wide-Ranging Cellular Modem Support. Chances Are, You're Good to Go.

The MAX On-The-Go's four USB ports support more than 150 4G LTE / 3G modems used by a variety of carriers worldwide. Whatever you're using, it'll probably work without a hitch.

Cap- and Cost-Aware Routing. Minimized Expenses. Maximized Performance.

The MAX On-The-Go's bandwidth usage monitor allows you to prioritize connections by cost and data allowance. It automatically switches between connections to give you the best performance at the lowest cost, and you'll never again have to worry about expensive data overages.

Integrated and External Antennas. Extend Your Wi-Fi Range Anytime.

The MAX On-The-Go features a built-in omnidirectional antenna that lets you set up a Wi-Fi hotspot without carrying extra equipment. It also supports an external antenna using its RP-SMA connector, perfect for when you need a wider coverage area.

Specifications

-	
MAX On-The-Go	
WAN Interface	4x USB Interfaces 1x 10/100M Ethernet Port
LAN Interface	1x 10/100M Ethernet Port 802.11b/g/n 150 Mbps Wi-Fi Access Point
Wi-Fi AP Operating Frequency	2412 – 2472 MHz
Wi-Fi Antenna	Integrated 1dBi Omni Antenna Switchable to RP-SMA Connector for External Wi-Fi Antenna
Power Input	Device: 10V – 24V DC AC Adapter: AC Input 100V – 240V, DC Output 12V
Power Consumption	20W (max.)
Dimension	4.3 x 4.3 x 1.2 inches 110 x 110 x 30 mm
Weight	0.43 pound 195 grams
Operating Temperatu	-14° – 149°F -10° – 65°C
Humidity	15% – 95% (non-condensing)
Certifications	FCC, CE, RoHS

For the most updated specifications, please refer to our website: http://www.pepwave.com/max-mobile-router/.



For a list of supported modems, please refer to our website: http://www.pepwave.com/modem.







Features

Warranty

WAN

USB 4G / 3G Modem Support Support for PPPoE, Static IP, DHCP Support for Dynamic DNS services WAN Link Health Check Bandwidth Allowance Monitor

LAN

DHCP Server for LAN Clients Extended DHCP Options DHCP Reservation DNS Proxy for LAN Clients

Complete VPN Solution

PepVPN / SpeedFusion*
Site-to-Site VPN
Bandwidth Aggregation*
Hot Failover*
256-bit AES Encryption
Pre-shared Key Authentication
Dynamic Routing
IPsec VPN (Network-to-Network)

1-Year Limited Warranty

Load Balancing*

Intelligent Failover
Session Persistence
Per-Service Load Distribution
Multiple Algorithms

Networking

NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPnP, NAT-PMP WINS Server

Advanced QoS

User Groups
Individual Bandwidth Limit
Application Prioritization
SIP, HTTPS, VPN QoS
Custom Application QoS

Security

Stateful Firewall DoS Prevention

Device Management

Web Administrative Interface Command Line Interface InControl Cloud Management Email Notification Active Client & Session Lists Bandwidth Usage Statistics Web Reporting Services Syslog Service SNMP v1, v2c and v3

Certification

FCC, CE, RoHS

Product Ordering Information

MAX On-The-Go

Product Code	Description
MAX-OTG-U1	Single-USB4GLTE/3Grouter.SupportsPepVPN.UpgradabletoMAX-OTG-U4orMAX-OTG-SFwithlicensekey.
MAX-OTG-U4	Quad-USB4GLTE/3Grouter.SupportsPepVPNandquad-WANloadbalancing&failover.UpgradabletoMAX-OTG-SFwithlicensekey.
MAX-OTG-U4-SF	Quad-USB 4G LTE/3G router. Supports PepVPN with SpeedFusion Bandwidth Bonding and quad-WAN load balancing & failover.



POLAND

T: +48 22 382 53 75 E: sales@wilink.pl www.wilink.pl

^{*}Available on selected models.